

Item	Value
Pixel Pitch (mm)	7.6
Pixel Density (pixels/m ²)	17222
Pixel Configuration	SMD 3 in 1
Viewing Angle (H/V)	140 / 80 Deg.
Brightness (cd/m ²)	5500
Drive Mode	1 / 6 Scan
Grey Level (bit)	14
Refresh Rate (Hz)	> 1920
Module Size (mm)	320 (W) x 320 (H)
Module Size (inch)	12.60 (W) x 12.60 (H)
Module Resolution (pixels)	42 x 42
Panel Dimension (mm)	640 (W) x 640 (H) x 108 (D)
Panel Dimension (inch)	25.20(W) x 25.20(H) x 4.25(D)
Panel Resolution (pixels)	84 x 84
Panel Type and Material	Aluminum Alloy
Panel Weight (kg)	14.5
Hanging Panel Quantity (vertical)	15 panels
Voltage	AC 110 / 220
Avg. Power Consumption (W/m ²)	300 AC
Max. Power Consumption (W/m ²)	900 AC
Serviceability	Front / Rear
Protection Grade (Front/Rear)	IP65 / IP65
Operating Temp / Humidity (°C/%RH)	-20~ +50 / 10~90
Storage Temp / Humidity (°C/%RH)	-40~ +85 / 10~95
Lifetime (hours)	=50000 (Normal Temp)
Compliant Standard	CE,FCC,RoHS

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights reserved.